

WATER BASED INTERIOR PRODUCT GROUP

NIPPON PAINT PLASTIC GYPSUM PRIMER

PRODUCT DESCRIPTION

Ready-to-use transparent plaster surface primer that is designed specially to prevent the high absorptivity of plaster surfaces for plastic paints.

SPECIFICATIONS

Nippon Paint Plastic Interior Transparent Primer is required for priming before the application of plastic paints (Nippon Paint Aliza). Prevents the absorptivity of plaster surface and enables the paint to integrate with the surface thanks to its high penetration ability. Prevents the paint from drying too fast and saves money by decreasing paint consumption.

APPLICATION SURFACES

Applied on plaster, lime whitewash, low quality absorbent plastic painted surfaces that lost their quality, and highly absorbing and/or high dust generating surfaces like aerated concrete.

APPLICATION

Ensure that the application surface is smooth, firm and able to bear the primer and top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Observe the setting period (28 days) for concrete, exposed concrete and new plastered surfaces.

Apply the transparent primer on plaster or similar surfaces only after they are sanded and dusted with a moist cloth/moist car wash brush/broom. Ensure that the ambient and surface temperatures are between +5°C and +30°C during application and until the products are fully dried, and protect the surfaces against frost. Apply Nippon Paint Plastic Interior Transparent Primer using a brush or a roller without combing or polishing (by rolling the roller in one direction once) in a way that will not create a glassy surface. Dull the surface with sandpaper if a glassy surface is formed. Avoid airless spraying method.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

WARNING

There should not be any glassy layer on the surfaces that Nippon Paint Plastic Interior Transparent Primer is applied. Such glassy layers should be removed from the surface by sanding or mechanical methods, and the surface should be dulled. Otherwise, there may be peeling, cracking, blistering, roller tracks and coverage problems. It should be applied in a way that it will not create a film layer on the surface. Avoid the airless spraying method.

THINNING

Ready to use.

DRYING TIME (at 20°C, 65% RH)

Touch dryness: 1 hours

Paint application: 6 hours (drying time may increase at higher relative humidity and lower temperature)

CONSUMPTION

8-12 m² in a single coat per liter depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

15 L, 5 L

Pos. No.

Y.25.003/05, Y.25.003/06, Y.25.003/07, Y.25.003/11, Y.25.003/14, Y.25.003/15, Y.25.003/16, Y.25.003/17,
Y.25.003/18, Y.25.003/19, Y.25.003/20, Y.25.003/21, Y.25.003/22, Y.25.003/32, Y.25.003/33,
Y.25.003/34, Y.25.004/01, Y.25.004/02, Y.25.004/03, Y.25.004/10, Y.25.004/13, Y.25.005/01, Y.25.005/02,
Y.25.005/03, Y.25.005/04, Y.25.005/05, Y.25.005/06, Y.25.005/07, Y.25.005/08, Y.25.005/09

Rate No.

04,555/01

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.