

## WATER BASED INTERIOR PRODUCT GROUP

### NIPPON PAINT INTERIOR PLASTER

#### PRODUCT DESCRIPTION

Acrylic copolymer emulsion-based interior smoothing paste.

#### APPLICATION SURFACES

Can be used safely in correcting concrete and mineral-plastered, old-painted and rough surfaces on interior walls and in filling shrinkage cracks.

#### APPLICATION

Nippon Paint Interior Paste is ready-to-use. Prior to application, the surface should be free of dust, dirt and oils; bulges should be thoroughly rubbed off; and the surface should be dry. Interior paste should be applied after a coat of Nippon Paint Interior Transition Primer or Nippon Paint Interior Paste Primer on mineral-based rough cast interior surfaces with minimal absorbency and without dust emission, and after a coat of Nippon Paint Interior Transparent Primer on surfaces with high absorbency and dust generation. Nippon Paint Interior Paste should be applied by ensuring dryness between each coat using a spatula and a flexible steel trowel in a thickness of 1mm until surface smoothness is achieved. Drying period between coats is 2 to 4 hours. The surface can be sanded after 24 hours. All types of paint can be used for painting over with a suitable primer. Ensure that ambient and surface temperature stays between +5°C and +30°C throughout the application. New pasted surfaces must be protected from strong wind and sunlight. Used tools should be cleaned with water after the application.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

#### THINNING

Ready to use.

#### DRYING TIME (at 20°C, 65% RH)

Touch dryness: 1 hours

Final drying: 24 hours (drying time may increase at higher relative humidity and lower temperature)

#### CONSUMPTION

500-1500g/m<sup>2</sup> in a single coat depending on the type, absorbency and structure of the application surface. With 1 kilogram product, 0.75-2m<sup>2</sup> area can be pasted. Perform a controlled sample run to estimate the precise consumption amount.

#### STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

**PACKAGE:** 4 KG, 25 KG

#### Pos. No.

Y.25.003/14, Y.25.003/17, Y.25.003/20, Y.25.003/23, Y.25.003/26, Y.25.003/32

#### Rate No.

04,557/01



This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above.

Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

**This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.**

---

**BETEK BOYA VE KİMYA SANAYİ A.Ş.**

Zümrütevler Mahallesi Üral Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - [www.nipponboya.com](http://www.nipponboya.com)

