

## WOOD CARE PRODUCTS

### NIPPON PAINT GEL WOOD COLORANT

#### PRODUCT DESCRIPTION

Exterior wood colorant which provides application comfort with Nippon Paint Gel Wood Colorant, solvent-based, gel structure.

#### SPECIFICATIONS

Nippon Paint Gel Wooden Colorant does not drip and leak in application thanks to its gel structure. It creates a thin film, and enables the wood to breath. It is a reinforcer developed for exterior facades. Furthermore, it colors the wood before application without requiring impregnation. It provides resistance to ambient conditions, UV and water. It provides ease of application on vertical and ceiling surfaces where it is difficult to apply.

#### APPLICATION SURFACES

It is used on exterior wooden surfaces, exterior coats and pergolas. Moreover, they can be used for the impregnation and coloring of the surfaces such as doors and windows. It is not recommended for indoor use.

#### APPLICATION

Apply Nippon Paint Gel Wooden Colorant by means of a brush, without stirring and without thinning. The gel structure is lost for some time when it is stirred. It regains the gel form after a short time when it is left on its own. It should be applied in 2-3 coats. Apply in an environment between +5°C and +30°C. The moisture of the wood should be less than 15%. Note that the color gets darker as the number of coats increases. Apply the same number of coats in ongoing work.

Avoid applying products like linseed oil, synthetic paste and filler varnish to surfaces during substructure repairs.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

#### THINNING

Ready to use. Do not thin.

#### DRYING TIME (at 20°C, 65% RH)

The 2nd coat can be applied 12 hours later (drying time may increase at higher relative humidity and lower temperature).

#### CONSUMPTION

Can be applied on an area of 11-14 m<sup>2</sup> in a single coat with 1 Liter based on the type and absorbency of the wood. Color and consumption may vary depending on the wood type, surface state, number of coats and application method. Perform a controlled sample run to estimate the precise consumption amount.

#### FLASH POINT

< 41°C

#### STORAGE

It can be stored in its unopened package for 2 years, in a cool and dry place, away from frost and direct sunlight at 5-30°C. Close the lid air-tight immediately after application. Consume the unpackaged product within 24 hours.

#### PACKAGE

2.5L

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

**This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.**