

CREATIVE EFFECT PRODUCT GROUP

NIPPON PAINT DUCHESSE SATIN EXTERIOR

PRODUCT DESCRIPTION

Water-based, acrylic copolymer emulsion-based, gloss, semi-covering, metallic-finish, decorative top-coat exterior paint.

APPLICATION SURFACES

Nippon Paint Duchesse Satin Exterior. should never be applied on smooth surfaces. It should be applied on the prepared surfaces with grained, acrylic or mineral-based coats.

APPLICATION

The appearance, brightness and color of the product varies according to the type and color of the material used for the surface.

Surfaces to be painted for the first time and surfaces with old paint; apply the matching color of Nippon Paint Aquatic Grained to the color of the last coat as the first coat on surfaces primed with Nippon Paint Silicone Exterior Primer. If the surface to be applied is textured, paint it with Nippon Paint Aquatic Silicone Exterior Paint that matches the top coat color after the primer application. Apply the paint with a roller for exterior surfaces.

In order to prevent problems that arise from early drying; the paint should not be applied in direct sunlight, wind or other negative climate conditions. Pay attention for the application surface and ambient temperatures to be between +5°C and +30°C. The paint must be applied by a large team, and the application surface must be finished in one piece using natural joints.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

CAUTION:

Apply between +10°C and +30°C.

Never dilute it.

TECHNICAL SPECIFICATIONS:

Color: Selected from Nippon Paint Duchesse Satin Exterior color chart.

Density: 1.05 ± 0.05 g/ml

THINNING

Ready to use.

DRYING TIME (at 20°C, 65% RH)

First drying: 45 minutes Final dry: 24 hours

CONSUMPTION

80-110 ml/m² per coat depending on the condition of the surface. 1 Liter covers a 9– 12 m² space with one coat. Perform a controlled sample run to estimate the precise consumption.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

13.5 L, 2.5 L, 1.25 L



This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Üral Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com

