

CREATIVE EFFECT PRODUCT GROUP

NIPPON PAINT RUSTY

PRODUCT DESCRIPTION

Water-based, rusty and antique metal effect, decorative top coat interior paint.

APPLICATION

Different patterns may be obtained with different application methods. The Nippon Paint Rusty is ready to use and the product should never be thinned. Never apply in wide movements during application. We recommend the application two coats to obtain the desired look and color for the Nippon Paint Rusty product.

The surface to be applied with Nippon Paint Rusty should be smooth, stable, dry and self-supporting. The surface must absolutely be smoothened and flattened with Nippon Paint Interior Paste. For surface preparation, never use satin plaster due to its weak and dust-generating texture.

Apply Nippon Paint Interior Paste Primer on the surface with a roller. Apply Nippon Paint Rusty over it with a brush in short and cross-hatch movements. Apply to the surface with short and diagonal movements by taking a small amount on the suede effect brush. Never apply the product densely or in a manner that leaves small particles.

Wait for 15- 20 minutes after application, then compress with the Nippon Paint Rusty steel trowel with cross-hatch movements with light pressure to give the final pattern. Wait for a minimum of 8 hours between coats. Apply the second coat in the same way as the first. After the second coat , wait for 25-30 minutes before compressing the product.

Caution: 1 hour after coloring Nippon Paint Rusty, shake the product manually, without putting in a mixer, or stir manually with a stirring rod. Otherwise, the particles in the product are lost due to fast and exaggerated mixing, and the desired pattern cannot be obtained.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

TECHNICAL SPECIFICATIONS

Color: Choose from Nippon Paint Rusty color card.

Density: 1.05 ± 0.05 g/ml

THINNING

Ready to use.

DRYING TIME (at 20°C, 65% RH)

First drying: 1 hours. Between coats. 8 hours. Final dry: 24 hours

CONSUMPTION

Between 200-240 gr/m² for a single coat depending on the evenness and absorbency of the surface. An area of 4 – 5 m² can be painted in a single coat with 1 kg. Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

2.5 L, 1.25 L



This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Üral Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com

