

FUNCTIONAL PRODUCT GROUP

NIPPON PAINT SKETCHY WHITEBOARD PAINT

PRODUCT DESCRIPTION

Transparent interior paint which turns the applied surface into a whiteboard and allows for writing with boardmarkers.

SPECIFICATIONS

With Nippon Paint Sketchy, you can turn a smooth surface into a high quality whiteboard suitable for dense use. With the transparent structure of the product, you can obtain not only white sketching boards, but in the same color as your wall.

APPLICATION SURFACES

The surface should be clean, dry, free of grease and smooth. Sand before and wipe with a dry cloth where required. Remove any oil, paint residues or dusts off the surface completely. Avoid irregular and absorbing surfaces. Nippon Paint Sketchy can be applied on stone, wood, rigid plastic and metal. Nippon Paint Sketchy is a transparent material; therefore the substrate should be painted in the desired color before its application.

APPLICATION

Nippon Paint Sketchy can be used both at home and office. It is convenient for any space; from the living room to the bedroom, meeting room to the office or public buildings such as schools. Nippon Paint Sketchy allows you to define the area, shape and dimensions to be used for sketching. You can use boardmarkers to write on the painted surface. It can easily be cleaned with a soft cloth or a whiteboard eraser. The smoother the surface, the easier to clean. Use a lint-free short-hair roller. After using, clean the equipment immediately with a brush cleaner. If there is a masking tape, remove it immediately after painting. Do not use Nippon Paint Sketchy at any places where the temperature is less than +10°C and/or relative humidity is more than 80%. To obtain the best result, make sure that the wall is covered enough. Allow for sufficient ventilation during application.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

THINNING

Stir the package content thoroughly before application. Ready to use. You can dilute the paint by 3% with white spirit where required.

DRYING TIME (at 20°C, 65% RH)

Curing time of Nippon Paint Sketchy is approximately 1 hour. The painted surface becomes available for use 24 hours later.

CONSUMPTION

Ranges between 3.5- 4 m² per 0.25 L for single coat depending on surface absorbency. Perform a controlled sample run to estimate the precise consumption.

STORAGE

Has minimum 12 months shelf life if stored in a cool and dry place at 5 to 35°C / 40 to 75°F temperature. Keep away from direct sunlight and close the package tightly. Keep out of the reach of children.

PACKAGE

0.25 L



This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder. Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Üral Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com

