

## WOOD CARE PRODUCTS

### NIPPON PAINT WOOD COLORANT

#### PRODUCT DESCRIPTION

A modified alkyd resin-based, decorative wood colorant with high penetration power.

#### SPECIFICATIONS

Nippon Paint Wood Colorant penetrates deeply into the wood with its high penetration strength. Dries fast, adjusts moisture and can be shaped perfectly. It is ideal for wooden parquets particularly.

#### APPLICATION SURFACES

Developed for coloring indoor wooden surfaces. The shade of surface color may differ depending on the type of wood and the number of coats applied.

#### APPLICATION

Nippon Paint Wood Colorant is ready-to-use. Recommended to be stirred before application. Clean previously painted surfaces completely. Remove dirt like resin and sand dust on wood surfaces that will be painted for the first time. Nippon Paint Wood Colorant can be applied with a brush, sponge or cloth. The moisture of the wood should be less than 15%. Ensure that the application surface and ambient temperatures are between +5°C and +30°C. Note that the color gets darker as the number of coats increases. Apply the same number of coats in ongoing work.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

#### THINNING

Ready to use. Do not thin.

#### DRYING TIME (at 20°C, 65% RH)

Hard-dry: 12 hours (drying time may increase at higher relative humidity and lower temperature)

On the application: For solvent-based varnish: 24 hours; Water-based varnish: 48 hours.

#### CONSUMPTION

Can be applied on an area of 8-12 m<sup>2</sup> in a single coat with 1 Liter based on the type and absorbency of the wood. Color and consumption may vary depending on the wood type, surface state, number of coats and application method. Perform a controlled sample run to estimate the precise consumption amount.

#### FLASH POINT

41°C

#### STORAGE

It can be stored in its unopened package, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

#### PACKAGE

15 L, 2.5 L

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

**This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.**