

WOOD CARE PRODUCTS

NIPPON PAINT GARDEN FURNITURE TEAK OIL

PRODUCT DESCRIPTION

Nippon Paint Garden Furniture Care Oil is a high quality care oil that is manufactured with exclusively selected mixture of natural oil, specially developed for maintaining hard woods such as teak and it can be applied to other type of woods.

SPECIFICATIONS

With its wax formula, Nippon Paint Garden Furniture Care Oil provides protection of wood against water and prolongs its life. It replaces the natural oils of the wooden surface that decrease over time as result of weather conditions and strengthens it. It is easily applied and penetrates the wood quickly. It does not create a coating layer on the surface. Provides care without compromising the natural look of the wood.

APPLICATION SURFACES

It can be used on all types of exterior wooden surfaces, garden furniture, garden parquets, swimming pool edges, floor coverings, and materials produced from hardwood (teak, iroko, etc.) like vessels (e.g. ship, boat) decks and piers.

APPLICATION

Nippon Paint Garden Furniture Care Oil is ready to use. Mix thoroughly before applying. Clean the application surfaces from oil, dirt, resin and dust, and remove old paint and varnish residues. Before applying on wooden surfaces containing high concentrations of natural oil like teak and iroko, the surface must be wiped with cellulose thinner to remove the oil. After this procedure, sanding can be performed. For application, use an appropriate brush and a lint-free soft, dry cloth. For the first coat, oil must be applied with the brush evenly and in the direction of wood grains and the wood must be saturated with oil. Approximately 15 minutes later, excess oil on the surface must be wiped with a clean cloth. This process ensures the oil is evenly spread on and absorbed by the wooden surface. It is recommended that the teak oil be applied in two thin coats.

On raw wood surfaces, the wood is sanded in the direction of the grains (150- 180 grit sandpaper can be used) and cleaned from any particles.

Before application on wood, the wood is recommended to be impregnated with 1-2 coats of Nippon Paint Wooden Impregnation Agent. After 24 hours, Nippon Paint Garden Furniture Care Oil can be applied.

On old wooden surfaces (unpainted wood), sand the surface until the clean wooden surface becomes visible. After that, transparent Nippon Paint Wood Impregnation Agent and Nippon Paint Garden Furniture Care Oil should be applied.

Repeat the application of Nippon Paint Garden Furniture Care Oil 1- 2 times a year depending on the weather conditions. Single coat of Nippon Paint Garden Furniture Care Oil is enough for care process.

CAUTION: Before application, the surface must be thoroughly cleaned of dirt, oil and resin. The temperature must be between +5°C and +35°C for application. Do not apply under direct sunlight and in rainy weather. Ensure that the humidity of the application wood is not over 15%.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

THINNING

Ready to use. Do not thin.

DRYING TIME (at 20°C, 65% RH)

Hard-dry: Max. 24 hours (drying time can increase at higher relative humidity and lower temperature values).

Wait for 8 hours minimum between each coat.

CONSUMPTION

Can be applied on an area of 18-22 m² in a single coat with 1 Liter based on the type and absorbency of the wood. Color and consumption may vary depending on the wood type, surface state, number of coats and application method. Perform a controlled sample run to estimate the precise consumption amount.

FLASH POINT

36°C

STORAGE

It can be stored in its unopened package, in a cool and dry place, away from frost and direct sunlight. Close the lid air-tight immediately after application.

PACKAGE

15 L, 2.5 L

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided hereinabove. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided hereunder.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.