



WATER BASED INTERIOR PRODUCT GROUP

NIPPON PAINT A+ CEILING PAINT

PRODUCT DESCRIPTION

An acrylic-emulsion based, white, specially-formulated, interior, decorative ceiling paint.

SPECIFICATIONS

Matte and smooth finish. Non-bloating and non-peeling, high inhalation capacity paint

APPLICATION

Ensure the surface that Nippon Paint A+ Ceiling Paint will be applied on is even, stable, dry, clean and able to bear the paint. Ensure that ambient and surface temperature stays between +5°C and +30°C throughout the application. Can be applied with either a brush, roller or spray gun. Apply Nippon Paint Interior Plastic Transparent Primer on absorbing and high dust generating surfaces like lime, plaster and whitewash before combing and polishing. Nippon Paint Interior Transition Primer or Nippon Paint Interior Paste Primer is recommended for surfaces with non-dusting old paint or plaster.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568.

Airless Spraying:

Pressure: 120-140 bars Nozzle Angle: 50°

Nozzle Size (inch): 0.019" Thinning: 10%

THINNING

Recommended to be applied in minimum two coats after thinning by 25% with clean water in brush and roller applications.

DRYING TIME (at 20°C, 65% RH)

Touch dryness: 1 hour

Resting period between coats: 6 hours

Final drying: 24 hours (drying time may increase at higher relative humidity and lower temperature)

Note: Don't start the application of the second coat before 4 hours. Maximum coverage is obtained when waiting-period is observed and the surface is primed. Surfaces must be protected from frost until fully dry.

CONSUMPTION

100-130g/m² in a single coat depending on the type, absorbency and structure of the application surface.

1 kg of paint covers a 7.5- 10 m² area with one coat.

Perform a controlled sample run to estimate the precise consumption amount.

STORAGE

It can be stored in its unopened package for 3 years, in a cool and dry place, away from frost and direct sunlight.

Close the lid air-tight immediately after application.

PACKAGE

20 KG, 17.5 KG, 10 KG, 3.5 KG

BETEK BOYA VE KİMYA SANAYİ A.Ş.

Zümrütevler Mahallesi Üral Sokak No:38 34852 Maltepe / İSTANBUL

Tel: 0216 571 10 00 Faks: 0216 571 13 15 Mersis No: 0167001238900018 - www.nipponboya.com





Conforms to TS 5808/2012



Conforms to the G communiqué

Gloss: Matt

Granule Size: Fine

Coverage Strength: Class 2 (7m²/L)

Wet Scrub Resistance: Class 4

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above.

Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.